



DATA SHEET FOR
TRANSFORMER # 906.1202

Made for STANDARD

LEADS	SCHEMATIC	LEADS
S#18/12" 0V	WHITE	BROWN 0V
S#18/12" 100V	BLUE	A/R THERMAL FUSE 120°C
S#18/12" 120V	YELLOW	UO = 128.0V RMS
S#18/12" 0V	ORANGE	120V RMS / 300VA
S#18/12" 100V	RED	ORANGE 0V
S#18/12" 120V	BLACK	A/R THERMAL FUSE 120°C
		UO = 128.0V RMS
		120V RMS / 300VA
		YELLOW 120V RMS / 300VA
		VIOLET STATIC SHIELD

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 6.5/5.4/3.0/2.7A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 62°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 6.5"	WASHER/PADS = 145 mm	CORE # 900622
H = 2.6"	THICKNESS = 0.08"	NO-LOAD LOSS = 3.1 W
WEIGHT = 10.5 LBS.	HOLE DIAMETER = .40"	NO-LOAD AMPS = 28 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. RoHS compliant. Leakage current < 100µA.

Label:		
SPEC DATE: 04/09/21	Transformer # B04315234 (906.1202)	Input Volt: 100/120/200/220/240V
(Logo)	Input Current: 6.5/5.4/3.3/3.0/2.7A	
By: <i>mx</i>	(date code)	

TOROID CORPORATION