



DATA SHEET FOR
TRANSFORMER # 908.1201

Made for STANDARD

page 1 of 1

<u>LEADS</u>			<u>SCHEMATIC</u>	<u>LEADS</u>			
S#18/12"	0V	WHITE		WHITE	0V	S#16/12"	
S#18/12"	100V	BLUE		A/R THERMAL FUSE 120° C			
S#18/12"	120V	YELLOW		BLACK	120V RMS / 760VA		S#16/12"
S#18/12"	0V	ORANGE		VIOLET	STATIC SHIELD		S#20/12"
S#18/12"	100V	RED					
S#18/12"	120V	BLACK					

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 8.0/6.7/3.7/3.4A
 RATED FREQUENCY: 50/60Hz
 TEMP. RISE AT RATED LOAD: 64° C

DIMENSIONS/WEIGHT:

OD = 6.5"
 H = 2.8"
 WEIGHT = 13.0 LBS.

MOUNTING:

WASHER/PADS = 145 mm.
 THICKNESS = 0.08"
 HOLE DIAMETER = 0.40"

CORE DATA:

CORE # 800
 CORE LOSS = 3.5 W
 NO-LOAD CURRENT = 31.9 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:
 Transformer # B04316195 (908.1201)
 Input Volt: 100/120/200/220/240V
 Input Current: 8.1/6.7/4.1/3.7/3.4A

SPEC DATE: 12/17/20

(Logo) (date code)

By: *mx*

TOROID CORPORATION