



DATA SHEET FOR
TRANSFORMER # 908.1202

Made for STANDARD

LEADS	SCHEMATIC	LEADS
S#16/12" 0V	WHITE	S#18/12"
S#16/12" 100V	BLUE	S#18/12"
S#16/12" 120V	YELLOW	S#18/12"
S#16/12" 0V	ORANGE	S#18/12"
S#16/12" 100V	RED	S#18/12"
S#16/12" 120V	BLACK	S#18/12"

BROWN 0V

A/R THERMAL FUSE 120°C
UO = 126.4V RMS

RED 120V RMS / 380VA

ORANGE 0V

A/R THERMAL FUSE 120°C
UO = 126.4V RMS

YELLOW 120V RMS / 380VA

VIOLET STATIC SHIELD

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 8.1/6.7/3.7/3.4A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 63°C

DIMENSIONS/WEIGHT:
 OD = 6.5"
 H = 2.8"
 WEIGHT = 12.5 LBS.

MOUNTING:
 WASHER/PADS = 145mm
 THICKNESS = 0.08"
 HOLE DIAMETER = .40"

CORE DATA:
 CORE # 800
 NO-LOAD LOSS = 3.5 W
 NO-LOAD AMPS = 31 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, CUL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

SPEC DATE: 12/17/20 By: <i>mx</i>	Label: (Logo)	<div style="text-align: right;"> </div> Transformer # B04315233 (908.1202) Input Volt: 100/120/200/220/240V Input Current: 8.1/6.7/4.1/3.7/3.4A (date code)
------------------------------------------	----------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

TOROID CORPORATION