



DATA SHEET FOR
TRANSFORMER # 910.1201

Made for STANDARD

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
S#16/12" 0V	WHITE	S#14/12"
S#16/12" 100V	BLUE	S#14/12"
S#16/12" 120V	YELLOW	S#18/12"
S#16/12" 0V	ORANGE	
S#16/12" 100V	RED	
S#16/12" 120V	BLACK	

WHITE 0V

A/R THERMAL FUSE 120°C

 UO = 124.5V RMS

BLACK 120V RMS / 1000VA

VIOLET 0V

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 10.5/8.7/4.8/4.4A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 58°C

DIMENSIONS/WEIGHT:
 OD = 6.6"
 H = 3.7"
 WEIGHT = 17.2 LBS.

MOUNTING:
 SPECIFIED BY CUSTOMER

CORE DATA:
 CORE # 1200
 NO-LOAD LOSS = 5.3 W
 NO-LOAD AMPS = 48 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, AAMI ES60601.1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. RoHS compliant. Leakage current < 100µA.

Label:		
SPEC DATE: 04/09/21	Transformer # B04316196 (910.1201)	Input Volt: 100/120/200/220/240V
	Input Current: 11/9/6/5/5A	
(Logo)		(date code)
By: <i>mx</i>		

TOROID CORPORATION