



DATA SHEET FOR  
TRANSFORMER # 915.1202

Made for STANDARD

LEADS	SCHEMATIC	LEADS
S#14/12"    0V	WHITE	BROWN    0V
S#14/12"    100V	BLUE	A/R THERMAL FUSE 120°C
S#14/12"    120V	YELLOW	UO = 124.5V RMS
S#14/12"    0V	ORANGE	120V RMS / 750VA
S#14/12"    100V	RED	ORANGE    0V
S#14/12"    120V	BLACK	A/R THERMAL FUSE 120°C
		UO = 124.5V RMS
		120V RMS / 750VA
		YELLOW    120V RMS / 750VA
		VIOLET    STATIC SHIELD

PRIMARIES ARE INSIDE A SLEEVE.  
Primaries must be connected together in series or in parallel.  
 LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY:            100/120/220/240V +/-10%  
 RATED PRIMARY CURRENT: 15.7/13.0/7.1/6.5A  
 RATED FREQUENCY:        50/60 Hz  
 TEMP. RISE AT RATED LOAD: 60°C

DIMENSIONS/WEIGHT:  
 OD = 9.0"  
 H = 3.7"  
 WEIGHT = 24.2 LBS.

MOUNTING:  
 SPECIFIED BY CUSTOMER

CORE DATA:  
 CORE # 1700  
 NO-LOAD LOSS = 6.7 W  
 NO-LOAD AMPS = 59 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer meets UL recognized UL 2601-1, AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. RoHS compliant. Leakage current < 100µA.

Label:		
SPEC DATE: 04/09/21	Transformer # B04313353 (915.1202)	Input Volt:    100/120/200/220/240V
	(Logo)	Input Current: 16/13/8/8/7A
By: <i>mx</i>		(date code)

**TOROID CORPORATION**