



DATA SHEET FOR
TRANSFORMER # 915.1202

Made for STANDARD

LEADS	SCHEMATIC	LEADS
S#14/12" 0V	WHITE	S#16/12"
S#14/12" 100V	BLUE	S#16/12"
S#14/12" 120V	YELLOW	S#16/12"
S#14/12" 0V	ORANGE	S#16/12"
S#14/12" 100V	RED	S#16/12"
S#14/12" 120V	BLACK	S#18/12"

	BROWN	0V		S#16/12"
		A/R THERMAL FUSE 120°C		
		UO = 124.5V RMS		
	RED	120V RMS / 750VA		S#16/12"
	ORANGE	0V		S#16/12"
		A/R THERMAL FUSE 120°C		
		UO = 124.5V RMS		
	YELLOW	120V RMS / 750VA		S#16/12"
	VIOLET	STATIC SHIELD		S#18/12"

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 15.7/13.0/7.1/6.5A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 60°C

DIMENSIONS/WEIGHT:
 OD = 9.0"
 H = 3.7"
 WEIGHT = 24.2 LBS.

MOUNTING:
 SPECIFIED BY CUSTOMER

CORE DATA:
 CORE # 1700
 NO-LOAD LOSS = 6.7 W
 NO-LOAD AMPS = 59 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer meets UL recognized UL 2601-1, AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

	Label:			
		Transformer # B04313353 (915.1202)		
SPEC DATE: 12/17/20		Input Volt: 100/120/200/220/240V		
		Input Current: 16/13/8/8/7A		
	(Logo)			
By: <i>mx</i>				(date code)

TOROID CORPORATION