



DATA SHEET FOR  
TRANSFORMER # 920.1201

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>			
S#12/12"	0V	WHITE		WHITE	0V	S#10/12"	
S#12/12"	100V	BLUE		A/R THERMAL FUSE 120° C	BLACK	120V RMS / 2000VA	S#10/12"
S#12/12"	120V	YELLOW		UO = 124.1V RMS	VIOLET	STATIC SHIELD	S#18/12"
S#12/12"	0V	ORANGE					
S#12/12"	100V	RED					
S#12/12"	120V	BLACK					

PRIMARIES ARE INSIDE A SLEEVE.  
Primaries must be connected together in series or in parallel.  
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%  
 RATED PRIMARY CURRENT: 20.8/17.3/9.5/8.7A  
 RATED FREQUENCY: 50/60Hz  
 TEMP. RISE AT RATED LOAD: 58° C


DIMENSIONS/WEIGHT:  
 OD = 9.2"  
 H = 4.1"  
 WEIGHT = 31.0 LBS.

MOUNTING:  
 SPECIFIED BY CUSTOMER

CORE DATA:  
 CORE # 902047  
 CORE LOSS = 8.4 W  
 NO-LOAD CURRENT = 71.7 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1. AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:   
 Transformer # B04316198 (920.1201)  
 Input Volt: 100/120/200/220/240V  
 Input Current: 21/18/11/10/9A

SPEC DATE: 12/17/20

(Logo)

By: *mx* (date code)

**TOROID CORPORATION**