

DATA SHEET FOR  
TRANSFORMER # 920.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>			
S#12/12"	0V	WHITE		BROWN	0V	S#12/12"	
S#12/12"	100V	BLUE		A/R THERMAL FUSE 120°C			
S#12/12"	120V	YELLOW		UO = 124.0V RMS	RED	120V RMS / 1000VA	S#12/12"
S#12/12"	0V	ORANGE			ORANGE	0V	S#12/12"
S#12/12"	100V	RED		A/R THERMAL FUSE 120°C	YELLOW	120V RMS / 1000VA	S#12/12"
S#12/12"	120V	BLACK			VIOLET	STATIC SHIELD	S#18/12"

PRIMARIES ARE INSIDE A SLEEVE.  
Primaries must be connected together in series or in parallel.  
LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%  
RATED PRIMARY CURRENT: 20.8/17.3/9.5/8.7A  
RATED FREQUENCY: 50/60 Hz  
TEMP. RISE AT RATED LOAD: 55°C


DIMENSIONS/WEIGHT:  
OD = 10.0"  
H = 4.0"  
WEIGHT = 32.5 LBS.

MOUNTING:  
SPECIFIED BY CUSTOMER

CORE DATA:  
CORE # 902002  
NO-LOAD LOSS = 8.4 W  
NO-LOAD AMPS = 72 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. RoHS compliant. Leakage current < 100µA.

Label:   
Transformer # B04313354 (920.1202)  
Input Volt: 100/120/200/220/240V  
Input Current: 21/18/11/10/9A

SPEC DATE: 04/09/21

(Logo)

By: *mx* (date code)

**TOROID CORPORATION**