



DATA SHEET FOR  
TRANSFORMER # 925.1201

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
S#12/12"	0V	WHITE		WHITE	0V	S#10/12"
S#12/12"	100V	BLUE		BLACK	UO = 123.1V RMS	S#10/12"
S#12/12"	120V	YELLOW		GRAY	120V RMS / 2500VA	S#18/12"
S#12/12"	0V	ORANGE		GRAY	A/R THERMAL FUSE 120° C/6A	S#18/12"
S#12/12"	100V	RED		VIOLET	STATIC SHIELD	S#18/12"
S#12/12"	120V	BLACK				

PRIMARIES ARE INSIDE A SLEEVE.  
Primaries must be connected together in series or in parallel.  
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%  
 RATED PRIMARY CURRENT: 26/22/12/11A  
 RATED FREQUENCY: 50/60Hz  
 TEMP. RISE AT RATED LOAD: 61° C

DIMENSIONS/WEIGHT:  
 OD = 10.0"  
 H = 4.1"  
 WEIGHT = 38.0 LBS.

MOUNTING:  
 SPECIFIED BY CUSTOMER

CORE DATA:  
 CORE # 902428  
 CORE LOSS = 10.2 W  
 NO-LOAD CURRENT = 86.5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. RoHS compliant. Leakage current < 100µA.

Label:   
 Transformer # B04316199 (925.1201)  
 Input Volt: 100/120/200/220/240V  
 Input Current: 26/22/13/12/11A  
 SPEC DATE: 04/09/21  
 (Logo) (date code)  
 By: *mx*

**TOROID CORPORATION**