



DATA SHEET FOR
TRANSFORMER # 930.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>			
S#12/12"	0V	WHITE		BROWN	0V	S#12/12"	
S#12/12"	100V	BLUE		A/R THERMAL FUSE 120°C			
S#12/12"	120V	YELLOW		UO = 122.2V RMS	RED	120V RMS / 1500VA	S#12/12"
S#12/12"	0V	ORANGE			ORANGE	0V	S#12/12"
S#12/12"	100V	RED		A/R THERMAL FUSE 120°C	YELLOW	120V RMS / 1500VA	S#12/12"
S#12/12"	120V	BLACK			VIOLET	STATIC SHIELD	S#18/12"

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
RATED PRIMARY CURRENT: 31/26/15/13A
RATED FREQUENCY: 50/60 Hz
TEMP. RISE AT RATED LOAD: 54°C

DIMENSIONS/WEIGHT:

OD = 11.0"

H = 4.5"

WEIGHT = 50.0 LBS.

MOUNTING:

SPECIFIED BY CUSTOMER

CORE DATA:

CORE # 902906

NO-LOAD LOSS = 13.3 W

NO-LOAD AMPS = 112 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. RoHS compliant. Leakage current < 100µA.

Label:



SPEC DATE: 04/09/21

Transformer # B04313356 (930.1202)
Input Volt: 100/120/200/220/240V
Input Current: 31/26/16/15/13A

(Logo)

By: *mx*

(date code)

TOROID CORPORATION