



DATA SHEET FOR
TRANSFORMER # 940.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>			
S#10/12"	0V	WHITE		BROWN	0V	S#10/12"	
S#10/12"	100V	BLUE		A/R THERMAL FUSE 120°C UO = 122.2V RMS			
S#10/12"	120V	YELLOW		120V RMS / 2000VA	RED		S#10/12"
S#10/12"	0V	ORANGE			ORANGE	0V	S#10/12"
S#10/12"	100V	RED		A/R THERMAL FUSE 120°C UO = 122.2V RMS	YELLOW	120V RMS / 2000VA	S#10/12"
S#10/12"	120V	BLACK			VIOLET	STATIC SHIELD	S#18/12"

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 41/35/19/18A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 55°C

DIMENSIONS/WEIGHT:
 OD = 12.0"
 H = 4.9"
 WEIGHT = 62.0 LBS.

MOUNTING:
 SPECIFIED BY CUSTOMER

CORE DATA:
 CORE # 903716
 NO-LOAD LOSS = 14.8 W
 NO-LOAD AMPS = 126 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL2601-1, AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. RoHS compliant. Leakage current < 100µA.

Label:



SPEC DATE: 04/09/21

Transformer # B04313357 (940.1202)
 Input Volt: 100/120/200/220/240V
 Input Current: 41/35/21/19/18A

(Logo)

By: *mx*

(date code)

TOROID CORPORATION