



DATA SHEET FOR
TRANSFORMER # 940.1202

Made for STANDARD

LEADS	SCHEMATIC	LEADS
S#10/12" 0V	WHITE	BROWN 0V
S#10/12" 100V	BLUE	A/R THERMAL FUSE 120°C
S#10/12" 120V	YELLOW	UO = 122.2V RMS
S#10/12" 0V	ORANGE	120V RMS / 2000VA
S#10/12" 100V	RED	S#10/12"
S#10/12" 120V	BLACK	S#18/12"

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 41/35/19/18A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 55°C

DIMENSIONS/WEIGHT:
 OD = 12.0"
 H = 4.9"
 WEIGHT = 62.0 LBS.

MOUNTING:
 SPECIFIED BY CUSTOMER

CORE DATA:
 CORE # 903716
 NO-LOAD LOSS = 14.8 W
 NO-LOAD AMPS = 126 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL544 and UL 2601-1. CSA certified to CSA C22.2 No. 66 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:



SPEC DATE: 12/17/20

Transformer # B04313357 (940.1202)
 Input Volt: 100/120/200/220/240V
 Input Current: 41/35/21/19/18A

(Logo)

By: *mx*

(date code)

TOROID CORPORATION