



DATA SHEET FOR
TRANSFORMER # 950.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
S#10/18"	0V	WHITE		BROWN	0V	S#10/18"
S#10/18"	100V	BLUE		RED	UO = 122.1V RMS 120V RMS / 2500VA	S#10/18"
S#10/18"	120V	YELLOW		ORANGE	0V	S#10/18"
S#10/18"	0V	ORANGE		YELLOW	UO = 122.1V RMS 120V RMS / 2500VA	S#10/18"
S#10/18"	100V	RED		GRAY	A/R THERMAL FUSE 120°C/20A	S#18/18"
S#10/18"	120V	BLACK		GRAY	STATIC SHIELD	S#18/18"

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%

RATED PRIMARY CURRENT: 52/43/24/22A

RATED FREQUENCY: 50/60Hz

TEMP. RISE AT RATED LOAD: 55°C

DIMENSIONS/WEIGHT:

OD = 12.5"

H = 5.0"

WEIGHT = 79.0 LBS.

MOUNTING:

SPECIFIED BY CUSTOMER

CORE DATA:

CORE # 904763

NO-LOAD LOSS = 20.2W

NO-LOAD AMPS = 171mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. RoHS compliant. Leakage current < 100µA.

Label:



Transformer # B04313358 (950.1202)

SPEC DATE: 04/09/21

Input Volt: 100/120/200/220/240V

Input Current: 52/43/26/24/22A

(Logo)

(date code)

By: *mx*

TOROID CORPORATION

2020 Northwood Drive * Salisbury, MD 21801 * Tel: 410-860-0300 * Fax: 410-860-0302

e-mail: sales@toroid.com * web: www.toroid.com