



DATA SHEET FOR
TRANSFORMER # BT1000X


Made for STANDARD

page 1 of 1

LEADS

SCHEMATIC

LEADS

S#12/12"	0V	WHITE		WHITE	60V RMS / 500VA	S#12/12"
A/R Thermal Fuse 120° C				GREEN	0V	S#14/12"
S#12/12"	120V	BLACK		BLACK	60V RMS / 500VA	S#12/12"
				GRN/YEL	STATIC SHIELD	S#16/12"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
RATED PRIMARY CURRENT: 8.6A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 39 °C

DIMENSIONS/WEIGHT:
OD = 7.2"
H = 3.2"
WEIGHT = 20 LBS.

MOUNTING:
PER CUSTOMER REQUEST

CORE DATA:
CORE # 901065
CORE LOSS = 5.3 W
NO-LOAD CURRENT = 103 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer meets UL 506 and CSA C22.2 No. 66 standards.
Class B insulation.

Label:

SPEC DATE: 12/18/20

(Logo)

Transformer # BT1000X
PRI: 120V 60Hz, WHT-BLK
SEC: 60+60V 1000VA WHT-GRN-BLK

By: *mx*

(date code)

TOROID CORPORATION